
NI-9145 Specifications

2023-03-15



Contents

| | |
|-----------------------------|---|
| NI-9145 Specifications..... | 3 |
|-----------------------------|---|

NI-9145 Specifications

Definitions

Warranted specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

Characteristics describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are **Typical** unless otherwise noted.

Conditions

Specifications are valid for the range -40 °C to 70 °C unless otherwise noted.

Network

| | |
|--------------------------|--------------------|
| Network interface | 100BaseTX Ethernet |
| Compatibility | EtherCAT |
| Communication rates | 100 Mb/s |
| Maximum cabling distance | 100 m/segment |

Reconfigurable FPGA

| | |
|--|--|
| Type | Xilinx Zynq-7000, XC7Z020 All Programmable SoC |
| Number of logic cells | 85,000 |
| Number of flip-flops | 106,400 |
| Number of 6-input LUTs | 53,200 |
| Number of DSP slices (18 × 25 multipliers) | 220 |
| Available block RAM | 4480 kbits |

Safety Voltages

Connect only voltages that are below these limits.

| | |
|--------------------------|--------------------------------------|
| V terminal to C terminal | 30 V maximum, Measurement Category I |
|--------------------------|--------------------------------------|

Measurement Category



Caution Do not connect the product to signals or use for measurements within Measurement Categories II, III, or IV.



Attention Ne pas connecter le produit à des signaux dans les catégories de mesure II, III ou IV et ne pas l'utiliser pour effectuer des mesures dans ces catégories.

Warning Do not connect the product to signals or use for measurements within Measurement Categories II, III, or IV, or for

measurements on MAINS circuits or on circuits derived from Overvoltage Category II, III, or IV which may have transient overvoltages above what the product can withstand. The product must not be connected to circuits that have a maximum voltage above the continuous working voltage, relative to earth or to other channels, or this could damage and defeat the insulation. The product can only withstand transients up to the transient overvoltage rating without breakdown or damage to the insulation. An analysis of the working voltages, loop impedances, temporary overvoltages, and transient overvoltages in the system must be conducted prior to making measurements.

Mise en garde Ne pas connecter le produit à des signaux dans les catégories de mesure II, III ou IV et ne pas l'utiliser pour des mesures dans ces catégories, ou des mesures sur secteur ou sur des circuits dérivés de surtensions de catégorie II, III ou IV pouvant présenter des surtensions transitoires supérieures à ce que le produit peut supporter. Le produit ne doit pas être raccordé à des circuits ayant une tension maximale supérieure à la tension de fonctionnement continu, par rapport à la terre ou à d'autres voies, sous peine d'endommager et de compromettre l'isolation. Le produit peut tomber en panne et son isolation risque d'être endommagée si les tensions transitoires dépassent la surtension transitoire nominale. Une analyse des tensions de fonctionnement, des impédances de boucle, des surtensions temporaires et des surtensions transitoires dans le système doit être effectuée avant de procéder à des mesures.

Measurement Category I is for measurements performed on circuits not directly connected to the electrical distribution system referred to as **MAINS** voltage. MAINS is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics.



Note Measurement Categories CAT I and CAT O are equivalent. These test and measurement circuits are for other circuits not intended for direct connection to the MAINS building installations of Measurement Categories CAT II, CAT III, or CAT IV.

Environmental Characteristics

| Temperature | |
|----------------------------|---|
| Operating | -40 °C to 70 °C |
| Storage | -40 °C to 85 °C |
| Humidity | |
| Operating | 10% RH to 90% RH, noncondensing |
| Storage | 5% RH to 95% RH, noncondensing |
| Ingress protection | IP40 |
| Pollution Degree | 2 |
| Maximum altitude | 5,000 m |
| Shock and Vibration | |
| Operating vibration | |
| Random | 5 g RMS, 10 Hz to 500 Hz |
| Sinusoidal | 5 g, 10 Hz to 500 Hz |
| Operating shock | 30 g, 11 ms half sine; 50 g, 3 ms half sine; 18 shocks at 6 orientations |

Indoor use only.

Power Requirements



Caution The product must be powered with an AC adapter offered by NI or an approved Limited Energy, LPS, or Class 2 supply that meets the power requirements for the product and has appropriate safety certification marks for country of use.



Attention Le produit doit être alimenté par un adaptateur secteur proposé par NI ou une source d'alimentation de classe 2, à énergie et puissance limitées (LPS), qui répond aux exigences d'alimentation du produit et possède les marques de certification de sécurité appropriées pour le pays d'utilisation.

| | |
|--------------------------|--------------|
| Recommended power supply | 20 W, 24 VDC |
| Power consumption | 16 W maximum |
| Voltage input range | 9 V to 30 V |

Physical Characteristics



Tip For two-dimensional drawings and three-dimensional models of the NI-9145, visit ni.com/dimensions and search by module number.

| | |
|-----------------------|--|
| Weight (unloaded) | 980 g (34.6 oz) |
| Dimensions (unloaded) | 272.8 mm × 88.1 mm × 62.3 mm (10.74 in. × 3.47 in. × 2.45 in.) |

| Screw-terminal wiring | |
|------------------------------|---|
| Gauge | 0.2 mm ² to 2.1 mm ² (24 AWG to 14 AWG) copper conductor wire |
| Wire strip length | 6 mm (0.24 in.) of insulation stripped from the end |
| Temperature rating | 85 °C |
| Torque for screw terminals | 0.20 N · m to 0.25 N · m (1.8 lb · in. to 2.2 lb · in.) |
| Wires per screw terminal | One wire per screw terminal |
| Connector securement | |
| Securement type | Screw flanges provided |
| Torque for screw flanges | 0.3 N · m to 0.4 N · m (2.7 lb · in. to 3.5 lb · in.) |